

**PARTNER**

CARE . TRUST . RESPONSIBILITY

# POS System PT-5910

## Cost Effective Touch Terminal



The new PT-5910 POS Terminal is developed for business owners looking for practical, cost effective POS solution. The PT-5910 uses latest ATOM technology to ensure a high processing performance for its users and it is equipped with the top rated and energy-efficient ATOM D525 CPU.

**Special Features:**

- Intel Atom CPU 1.8 GHz
- Low Cost of Ownership
- DDR3 2x SODIMM slots 1GB
- Supports up to 4GB of Memory
- Supports Dual Displays (15" or 11.6" screen)
- Spill-proof resistant design

**Optional:**

- 3-track MSR
- Customer display module (2 x 20 VFD)
- Biometric reader, Smart Card Reader, I-Button, RFID reader

## POS System PT-5910

### Technical data

Item	PT-5910									
CPU Type	Intel®Atom™ Processor D525 (1M Cache, 1.8 GHz Dual Core)									
Chipset	Intel®NM10 Express									
LCD	15" active color TFT-LCD, resolution 1024 x 768									
Touch	5-wire Resistive touch (USB Interface)									
Memory	DDR3 2x SODIMM slots 1GB (up to 4 GB)									
LAN	10/100/1000 Gigabit Ethernet									
Storage	Internal 3.5" type SATA HDD or Internal SATA SSD 8GB x 1 (When Wall-mounted)									
I/O Interface	3 x COM ports 1 x DB-15 VGA port 1 x DB-25 for LPT port 1 x PS/2 Keyboard port 1 x PS/2 Mouse port 1 x RJ11 port 1 x RJ-45 LAN port with activity/ link and speed LEDs 3 x audio ports (1 x Line-in, 1 x Line-out , 1 x MIC-in) 4 x USB 2.0 ports 1 x DC +12V power adaptor connector									
Operation System	Windows 7, Windows XP, Linux (ubuntu, Fedora), WEPOS, POSReady,									
Power Supply	AC100~240V/DC12V, 7.5A, 90 watt power adaptor									
Dimensions	360 mm (W) x 246 mm (D) x 315 mm (H)									
Environment	<table border="1"> <thead> <tr> <th></th> <th>Operating</th> <th>Storage</th> </tr> </thead> <tbody> <tr> <td>Temperature</td> <td>0~45 °C</td> <td>-20~60 °C</td> </tr> <tr> <td>Humidity</td> <td>15% ~ 80%</td> <td>15% ~ 80%</td> </tr> </tbody> </table>		Operating	Storage	Temperature	0~45 °C	-20~60 °C	Humidity	15% ~ 80%	15% ~ 80%
	Operating	Storage								
Temperature	0~45 °C	-20~60 °C								
Humidity	15% ~ 80%	15% ~ 80%								
Certification	CE/FCC Class A, CCC, VCCI, LVD, KC									
Options	3-track MSR, Customer display module (2 x 20 VFD), Biometric Reader, Smart Card Reader, I-Button, RFID reader									



15-90 degrees tilt angle



Support Dual Display  
15" or 11.6"



Spill proof design



Support Pole mount Dual



Quick release latch design  
for easy maintenance



2 x 20 VFD Rear Display

